

SCDC SURFACE DRIVE

搭载发动机技术规格Engine Specification

品牌 Brand	型号 Model	功率 Power Kw/HP	转速 Speed (rpm)	气缸数/缸径/行程 Cylinder/Bore/Stroke	排气量 Displacement (L)	压缩比 Compression Ratio	进气 Inlet	燃油供给 Fuel Supply	油耗 (g/kw.h) Fuel consumption
SCDC	SD4105Z	85/115	3200	4/105-108	4.0	17.5:1	涡轮增压 Turbocharged	机械 Machinery	220
SCDC	SD4V25-955R	95/130	3400	4/92.94	2.5	17.5:1	涡轮增压 Turbocharged	电喷共轨 Common Rail	205
SCDC	SD4V25 1055R	105/143	3800	4/92*94	2.5	17.5:1	涡轮增压 Turbocharged	电喷共轨 Common Rail	205
SCDC	YC4FA115C-31	85/115	3100	4/92*100	2.66	16.3:1	涡轮增压 Turbocharged	机械 Machinery	220
SCDC	YC4FA130L-C20	95/130	3100	4/96*103	3.0	16.3:1	涡轮增压 Turbocharged	电喷共轨 Common Rail	230



SCDC SURFACE DRIVE

Application for Customs、Military、Patrol boat



Parameter \ Model	SCDC200S	SCDC200L	SCDC300	SCDC400	SCDC500
Length (mm)	950	980	1160	1360	1800
Max. Input Power (hp)	200	300	500	800	2000
Max. Input Speed (rpm)	3600	3000	2500	2500	2500
Max. Input Torque(N.m)	600	1320	2700	6500	10000
Steering Angle	40°	40°	40°	40°	36°
Trim Angle	15°	15°	15°	15°	15°
Weight (kg) Without propeller	~80	~90	~110	~180	~700
Body Material	S.S	S.S	S.S	S.S	S.S